



D5719-1 RADIUS BLOCK

NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.063 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027 OR ASTM B209
REF DART SPEC M6061T6S
OR: 6061-T6/T651/T6510/T6511/T62 ALUMINUM BAR
PER QQ-A-225/8 OR AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR
QQ-A-200/8 OR AMS-QQ-A-200/8 (OR AMS 4160) OR ASTM B211 OR ASTM B221
REF DART SPEC M6061T6B
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.7
7) WEIGHT: 0.01 lbs

RELEASED

2019 OCT 09
E.N. 14-118

APPROVED

A	NEW ISSUE		RF	19.07.19
REV.	DESCRIPTION		BY	DATE
DESIGN	RF	DART AEROSPACE USA, INC. HILLSBORO, OR		
DRAWN	RF			
CHECKED	PM	DRAWING NO. D5719		REV. A
MFG. APPR.	DD			SHEET 1 OF 1
APPROVED	VS	TITLE RADIUS BLOCK		SCALE
DE APPR.	DS			NTS
DATE	19.07.19	COPYRIGHT © 2019 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.		